



**Asound Realtek A-8110S 10/100/1000Mb
Gigabit LAN Card**

FEATURES	
<ul style="list-style-type: none"> ✦ Adheres to IEEE 802.3, 802.3u, and 802.3ab standards ✦ IEEE 802.3x Full-Duplex Flow Control support. ✦ IEEE 802.1p Layer 2 priority queuing support. ✦ IEEE 802.1q Virtual LAN (VLAN) Tag and Jumbo Frame support. ✦ PCI v2.2 32 bit, 33 MHz, 5-volt bus compliant. ✦ Auto-Negotiation support for Auto-Detect 10/100/1000Mbps data rate and Full/Half-Duplex operation mode. ✦ Automatic crossover support for crossover or regular cable. ✦ Wake-on-LAN and remote Wake-up support. (for PCI V2.2) 	
SPECIFICATIONS	
Model	10/100/1000Mbps Gigabit Ethernet PCI Bus Adapter (for 32bit Bus)
Standards	1000BASE-T: IEEE 802.3ab 100BASE-TX: IEEE 802.3u 10BASE-T: IEEE 802.3
Bus Type	PCI-Bus specification revision 2.2
Network Interface	One (1) shielded RJ-45 phone-type jack
Net Mode Supported	1000BASE-T: 4 pair Category 5 TP cable required 100BASE-TX: 2 pair Category 5 TP cable required 10BASE-T: 2 pair Category 3, 4, and 5 TP supported Full-Duplex available in three modes
LED indicators	Four green LEDs support for display 1000Link, 100Link, 10Link, Activity status
Environment	Operating Temperature: 0 - 55°C (32 - 131°F) Storage Temperature: -20° - +70°C (-4° - 158°F) Humidity: 10% - 90% Non -Condensing
Dimensions	119.9 x 51 mm (4.72x 2 inches)
PACKAGE CONTENT	
<p>This product package should contain:</p> <ul style="list-style-type: none"> ✦ One (1) single port Gigabit Ethernet PCI-Bus Adapter Card ✦ One (1) 3.5" Driver Diskette ✦ One (1) Warranty Card ✦ User's Guide 	

<< [Click here to go back to our modems and networking page for modems, NIC/LAN cards, and routers for sale....](#)
 << <http://www.OrpheusComputing.com/> computer upgrades and custom built computers homepage